


WON-330 | AUTOMATIC SLITTER REWINDER



The WON-330 narrow-web automatic slitter rewinder is fully servo-driven and features taper tension control, top brand web guiding, turret rewind, meter and number counting, static eliminator etc. The ultimate configuration for high productivity and quality.

WON-330	AVAILABLE WIDTH: 330MM/450MM/520MM		
	330	450	520
Max Web Width	330mm	450mm	520mm
Max Speed	300m/min	300m/min	300m/min
Max Unwind Dia.	700mm	700mm	700mm
Max Rewind Dia.	400mm	400mm	400mm
Auto Slit Precision	±0.2mm (automatic)	±0.2mm (automatic)	±0.2mm (automatic)
	±0.15mm (shear)	±0.15mm (shear)	±0.15mm (shear)
	±0.15mm (razor)	±0.15mm (razor)	±0.15mm (razor)
Min Slit Width	≥18mm (automatic)	≥18mm (automatic)	≥18mm (automatic)
	≥16mm (standard)	≥16mm (standard)	≥16mm (standard)
	≥11mm (razor)	≥11mm (razor)	≥11mm (razor)
Blades Installed	6 sets (included)	6 sets (included)	6 sets (included)
	10 sets (options)	10 sets (options)	10 sets (options)
Paper Path	3m	3m	4m
Air Supply	0.4-0.6MPa	0.4-0.6MPa	0.4-0.6MPa
Power Supply	3PH+N+PE	3PH+N+PE	3PH+N+PE
Total Motor Power	8KW	9KW	11KW
Dimension	1750 × 1230 × 1460	1750 × 1350 × 1460	2300 × 1600 × 1460
Weight	1300KGS	1600KGS	1900KGS

* May vary depending on selected options/configurations

UNWINDER & WEB GUIDING
Servo driven unwind for clock wise and anti-clock wise unwinding. Automatic tension control, end-of-roll detection, webguide, integrated splice table, 76mm unwind mandrel. Factory upgrade to unwind rolls with dia = 1000mm and a reel lift possible.

SEMI-AUTO TURRET
semi-automatic 2-spindle turret which will turn automatically, and lower a pressure arm upon reaching the counter set. Simple, effective and highly productive. Suitable for clock-wise and anti-clockwise rewinding.

COUNTER
High-quality German-made counting sensor - extra accessories needed for clear-on-clear material.

1 2 3


AUTOMATIC SLITTING
Automatically positioned slitting knives that are easy to control from the user-interface, including edge-trimming. Maximum of 10 knives allows for a wide range of slitting possibilities. Optionally add manual razor blade also.

JDF/JMF
Use Rhyguan's digital platform to receive JDF job data from your MIS/ERP system to automate settings and automatically pass-on JMF management information

SINGLE LAYER FILMS
Suitable to rewind thin films with optional Core-Lock differential rewind shafts. Slip threshold can be controlled from the touchscreen user panel. Lay-on rollers avoid air-bubbles during rewinding

WEB ADVANCE
The optional web advance comes with additional clamps. And is available for both the upper and lower rewind. The web advance can also function as a lay-on roller when rewinding filmic materials

WON-330 / SLITTER REWINDER



The WON-330 narrow-web slitter rewinder is fully servo-driven and features taper tension control, top brand web guiding, turret rewind, meter and number counting, static eliminator etc. The ultimate configuration for high productivity and quality.



WON-330

AVAILABLE WIDTH: 330MM/450MM/520MM

	S330	S450	S520
Max Web Width	330mm	450mm	520mm
Max Speed	300m/min	300m/min	300m/min
Min Slit width	16mm	16mm	16mm
Max Unwinder dia.	700mm	700mm	700mm
Max Rewinder dia.	400mm	400mm	400mm
Blades Installed	6 Sets	6 Sets	6 Sets
Air Supply	0.4~0.6MPa	0.4~0.6MPa	0.4~0.6MPa
Power Supply	3 PH+N+PE	3 PH+N+PE	3 PH+N+PE
Total Motor Power	7KW	7KW	10KW
Dimension	1800×1200×1400mm	1800×1320×1400mm	2265×1390×1400mm
Weight	1200KGS	1300KGS	1550KGS



UNWINDER & WEB GUIDING

Servo driven unwind for clock wise and anti-clock wise unwinding. Automatic tension control, end-of-roll detection, webguide, integrated splice table, 76mm unwind mandrel. Factory upgrade to unwind rolls with dia = 1000mm and a reel lift possible.

TURRET REWINDER

Rewinder with closed-loop tension control system ensures continuous stable tension. 400mm maximum rewind diameter.



COUNTER

High-quality German-made counting sensor - extra accessories needed for transparent film material.



SLITTING OPTIONS

Optional standard 6 shear slitter or razor blade slitter. Easy to install. Features a standard high pressure waste suction system.



Fully
Servo-Driven
Narrow-Web
Slitter
Rewinder

* May vary depending on selected options&configurations